



max power

MINIMUM SIZE



LITHIUM Deep Cycle *XTRA*

+Remco
ENERGY ANYWHERE



4x4 AUXILIARY



RV/CAMPING



INDUSTRIAL

The REMCO Lithium XTRA Super Slimline batteries are designed to fit where traditional shaped batteries can't.

A premium lithium battery, with a range of capacity choices, and the option to have an inbuilt DC-DC charger, REMCO Lithium XTRA Super Slimline is superior where space and performance are the key variables in a 2nd battery installation, perfect for those that need that little bit XTRA.

Key advantages of REMCO Deep Cycle XTRA



Australian engineered & built



Super slim size
Only 50mm to 85mm wide



Light Weight vs traditional batteries



Huge charge and discharge capability
Power more devices at once



Anderson connectors
Simpler and secure fitment



Aluminium enclosure
Increased strength vs plastic casing



In built DC charger options
75Ah, 110Ah & 150Ah models



Connect unlimited batteries in parallel

XTRA Triple Guard Protection

XTRA Tough Lithium Cells

Ultra durable hard case prismatic cells Locked together using a rigid PCB.

XTRA Safe BMS

Australian designed and tested:

- Short Circuit Protection
- Over and Under Voltage protection
- Over Current Protection
- Over and Under Temperature protection
- Cell Level Voltage protection
- Cell Balancing

XTRA Rugged Casing

Lightweight powder coated Aluminium:

- High melting point of 660°C
- Greater mechanical strength



Now with new 'Smart Sense Technology'.

Smart Sense uses ignition sensing instead of a voltage sensing relay to automatically signal a charging connection when your vehicle is turned on and detects when the vehicle is turned off to stop the charging process and avoid excess voltage drain of the primary battery common with most DC DC charger setups.

Code	Term	Volts	Ah C20	Max continuous current		Dimensions (mm)			Weight (KG)
				Discharge	Charge	Length	Width	Height	
RM12-75LFPXSL	Anderson	12	75	120A	120A	636	50	235	9.9
RM12-75LFPXSLSS	Anderson	12	75	120A	120A	636	50	235	9.9
RM12-110LFPXSL	Anderson	12	110	120A	120A	636	50	235	12.9
RM12-110LFPXSLSS	Anderson	12	110	120A	120A	636	50	235	12.9
RM12-150LFPXSL	M8	12	150	240A	240A	565	85	235	16.7
RM12-150LFPXSLSS	M8/Anderson	12	150	240A	240A	565	85	235	16.7